



Fully recessed mount

Partial recessed mount

Surface mount

Hoffman

SPECTRACOOTM SLIM FIT AIR CONDITIONERS

REDUCES COSTS AND MAINTENANCE

THREE SPACE-SAVING MOUNTING OPTIONS



FEATURES AND BENEFITS

- High-efficiency rotary compressor decreases operating costs
- Active condensate management prevents dripping water
- Remote access control option monitoring worldwide
- Dust-resistant coils for filterless operation save maintenance costs
- Easy filter replacement for extremely dusty environments
- Attractive aesthetics and optimized air flow

ENERGY EFFICIENT TO CONTROL OPERATING COSTS

- Cooling capacity: 1,000 to 13,500 BTU/Hr. (300 Watt to 4000 Watt)
- Voltage: 115 V, 230 V, and 400/460 V 3-phase (50/60 Hz)
- Protection class: UL Type 12, IP 54 (internal loop)
- Operating temperature range: 50° F to 131° F (10° C to 55° C)
- Slim depth with 3 mounting options: Fully recessed, partial recessed and surface mount
- Standard RAL 7035 light grey paint color

EASY TO MAINTAIN AND MONITOR

WORLDWIDE APPLICATIONS

Specially designed and developed to meet the requirements of worldwide industrial customers, easy to specify and easy to use.

From filterless operation to global certifications to our new remote access controller, the SpectraCool Slim Fit air conditioner makes automation cooling easy for system designers and operations maintenance teams around the world.

INDUSTRIAL APPLICATIONS: Machine tool, automotive, packaging systems, wood forming, factory robotics, material handling



Reduced maintenance:

- Optimized air flow
- Filterless operation



Easy fit:

- Front cover easy to remove
- Easy filter replacement when needed for extremely dusty applications



Simple, efficient monitoring:

Monitor and manage your industrial cooling simply from your pc or laptop